



## SONEXclassic™ Panels, Polyurethane

### SONEX® is effective.

SONEXclassic Panels have deep anechoic wedges specifically designed to scatter, deflect, and absorb sound energy in high traffic areas. Sound energy is redirected deep into the material where it is quietly converted to kinetic energy.

### SONEX is the original.

SONEX is the original and most recognized high performance noise control and acoustical treatment available. Its popularity results from the pattern's effectiveness and versatility. And even the liveliest areas can be controlled with the sound absorbing qualities of SONEX.

### SONEX is simple to install.

SONEX is designed to go up quickly and easily. Simply apply our AcouSTIC adhesive and press into place. You get a permanent seal and professional appearance quickly and easily.



Frequencies in Herz	Sound Absorption Coefficients*		
	2" thick	3" thick	3.75" thick
1250.09	0.15	0.19	
2500.29	0.42	0.59	
5000.64	0.99	1.14	
1000	0.97	1.14	1.16
2000	1.05	1.10	1.11
4000	0.97	1.10	1.15
NRC0.75	0.90	1.00	

\*Type B Mountings

### Product Specifications

Material:	Polyester urethane
Surface Pattern:	Pronounced sculpted surface
Density:	
Tensile Strength:	20 PSI
Flammability:	ASTM E-84 Class 2
Flame Spread:	2" thick - 75
	3" thick - 75
	3-3/4" thick - 300
Smoke Density:	2" - 340
	3" - 380
	3-3/4" - 450